

FLEX Soft Mirror

Technical Data Sheet



11 Bennet Avenue,
Melrose Park, SA 5039
Phone: (08) 8357 5444
info@dtktextiles.com.au
www.dtktextiles.com.au

FLEX SOFT MIRROR

is a cut material that has a soft filtered mirror finish and has a slight stretch too! Look no further than this incredible product, it is the thinnest vinyl we stock and is easy weed as well.

NOT Suitable for LAYERING.

Composition	Polyester
Thickness	70 Microns
Carrier	Polyester
Finish	Soft Filtered Mirror
Fabrics	Cotton, Polyester Blends, Cotton/Lycra Blends


CUTTER SPECIFICATIONS (GUIDELINES ONLY)

Blade	Standard 45°
Offset	
Mimaki 0.300	Roland 0.250
Blade Pressure	
Mimaki 50/70g (Protrusion 0.75mm)	Roland 70/90g
Minimum Text Size Of Cut	10mm

TECHNICAL INFORMATION



CUT



APPLICATION



AVAILABILITY



WASHING - 24HRS AFTER APPLICATION



APP TAPE

NOT REQUIRED

Application Instructions

1 CUT

EQUIPMENT/MATERIALS: Cutter

- If using a printer/cutter, ensure to set heaters to OFF.
- Feed vinyl into the cutter with the glue side facing upwards.
- Cut the design in 'mirror/reverse' on the glue side.
- Perform test cuts to ensure proper blade depth when cutting.
- Do not cut through the backing.
- 45° Blade for cutting is preferred for optimum result.
- The backing carrier should only be lightly scored when cutting.

2 WEED

EQUIPMENT/MATERIALS: Weeding tool.

- Weed away excess vinyl, i.e. anything that is not going to be applied to the garment.
- Only the desired vinyl should be left on backing sheet, ready for application.

3 PRESS

EQUIPMENT/MATERIALS: Heat press

- Pre Press Garment for 2-3 Seconds.
- Place transfer on garment in desired position, and heat press according to application guidelines.
- Once pressed, peel away clear carrier from the transfer (as per application guidelines).
- For best results and increased washability: After removing the backing, cover transfer with sheet of silicon/teflon or baking paper and perform a second press for 3-5 seconds.



APPLICATION NOTE:

Guidelines are provided as a recommendation only. They will vary depending on the machine, fabric and environmental conditions.

